



21UT Series VOGUE ULTRA UNIVERSAL 12 Floor Ceiling Indoor Unit



SPECIFICATIONS | 60Hz

21UT Series Vouge Ultra Universal 12 Floor Ceiling Indoor Unit
R22 & R410A Split System Cooling
Cooling Nominal : 24,000 - 60,000 Btuh (7.0- 17.5 kW)

INDOOR UNIT FEATURES

- ✓ 24 Volt Control Circuit
- ✓ Quiet Centrifugal Blower
- ✓ Painted Decorative Cabinet
- ✓ Accurator / Piston Refrigerant Control
- ✓ Clenable Cartridge Filters
- ✓ AUTO SWING (Vertical)
- ✓ EASY CONNECT Flare Connection

Notes:

1. Nominal capacities are based on ARI standards 210 / 240 - 89, air entering the indoor coil for cooling at 80/67 ° F (27/19 ° C) , DB/WB indoor & 95 ° F (35 ° C) ambient temperature, operating at high fan speed for 220-240 volt, 60 Hz operation.
2. Ratings are based on indoor and outdoor units connected by 16 ft (5 m) of tubing.
3. Refrigerant metering device is installed in the indoor unit as standard.
4. Flare fittings are provided for connecting indoor.
5. Insulation of suction line is required.
6. Outdoor units are shipped with full operating charge.
7. For details of model number nomenclature, please refer to publication DCTNOM-50314

PHYSICAL DATA							
MODEL NO.	21UT		024C	036C	048C	060C	
			24-070DWC	24-105DWC	24-140DWC	24-175DWC	
Cooling Capacity Nominal		Btuh (kW)	24,000 (7.0)	36,000 (10.5)	48,000 (14.0)	60,000 (17.5)	
Refrigerant Control			Accurator / Piston type @ Indoor unit				
INDOOR UNIT	Fan	Type	Centrifugal				
		Speed	3	3	3	3	
		Motor	HP	1/15	1/15	1/5	1/5
		Air Flow (H)	CFM (m³/hr)	710 (1200)	765 (1300)	1176 (2000)	1235 (2100)
		Noise Level (Hi)	dBA	45	48	50	52
Electrical	Voltage		208-230/1/60				
	Range		min 187 - max 253				
	FLA		0.65	0.65	1.6	1.6	
Controls			Wireless Microprocessor LCD Remote Control				
Refrigerant Type			R22/R410A				
Refrigerant	Type		Flare				
	Connections						
inches (mm)	Liquid		3/8 (9.5)	3/8 (9.5)	3/8 (9.5)	1/2 (12.7)	
	Suction		5/8 (15.9)	3/4 (19.1)	7/8 (22.1)	7/8 (22.1)	
Drain Connections inches (mm)			3/4 (19)				
Dimensions	Height		8 7/8 (225)	8 7/8 (225)	9 5/8 (245)	9 5/8 (245)	
	Width		48 (1220)	48 (1220)	55 7/8 (1420)	55 7/8 (1420)	
	Depth		27.6 (701)	27.6 (701)	27.6 (701)	27.6 (701)	
Net Weight lbs (kgs)			92 (41.5)	92 (41.5)	115 (52)	115 (52)	



DELTA Comfort Technologies LLC.
 3350 SW 48th Ave, Miramar, Florida.33027. USA
 Tel: 954 734 2708 Fax: 954 874 6999
www.deltacomforttechnologies.com
www.delta-dct.com

DCT Interamerica: Latin America-Mexico
 info@dctinteramerica.com

DCT America: North America, Canada
 info@dctamerica.com

DCT Europe: Europe, M.East, Africa
 info@dcteu.com

DCT China: Asia, Pacific, Russia
 info@dctchina.com

