



RESIDENTIAL

en-pro

Split Air Conditioners



21WG / WE SERIES ENPRO 12



PRODUCT FEATURES

- Rapid Cooling
- Auto Restart Capability
- LED Display
- Self Diagnostic
- Sleep Mode
- Whisper Quiet
- Modern Elegant Design
- Eco Refrigerant

BTU
12K-36K



ISO 14001

ISO 9001

SPECIFICATIONS | 60Hz

21WG / WE SERIES ENPRO 12
High Wall Cooling Systems
Split System Cooling Unit
Cooling: 12,000-36,000Btuh
(3.5-10.5kW)

INDOOR UNIT FEATURES

- ✓ WIRELESS LCD Remote Control
- ✓ AUTO setting for Cooling, Dehumidifying, Fan
- ✓ AUTO RESTART
- ✓ TIMER
- ✓ SLEEP Mode
- ✓ AUTO SWING (Vertical)
- ✓ TURBO Cooling Function
- ✓ LED Display
- ✓ Cleanable Cartridge Filters
- ✓ EASY CONNECT Flare Connections

OUTDOOR UNIT FEATURES

- ✓ ROTARY Compressor
- ✓ SUPER QUIET Operation
- ✓ 12.0 SEER in Cooling Mode.
- ✓ High Efficiency Cooling
- ✓ DURABLE CABINET with protective coating

Notes

1. Nominal capacities are based on ARI standards 210 / 240 - 89, air entering the indoor coil operating at high fan, speed for 220 volt, 60 Hz operation. Cooling: 80/67 ° F (27/19 ° C) DB/WB indoor & 95 ° F (35 ° C) ambient temperature.
2. Ratings are based on indoor and outdoor units connected by 16 ft (5 m) of tubing.
3. Refrigerant metering device is installed in the outdoor unit as standard.
4. Flare fittings are provided for connecting indoor and outdoor units.
5. Insulation of both liquid and suction line is required.
6. Outdoor units are shipped with full operating charge.
7. For details of model number nomenclature, please refer to publication DCTNOM-50314

PHYSICAL DATA							
I N D O O R	MODEL NO.	21W (G & E)	G012C 24-035BWC	G018C 24-053BWC	G024C 24-070BWC	E036C 24-105BWC	
	Cooling Capacity - Nominal	Btuh (kw)	12,000 (3.5)	18,000 (5.3)	24,000 (7.0)	36,000 (10.5)	
	Efficiency - SEER	Btuh/w (w/w)	12.0 (3.5)				
	Refrigerant Control	Capillary tube @ Outdoor Unit					
	Power Consumption (watts)		1,600	2,900	3,000	4,800	
	Fan	Type	Cross Flow Fan				
		Speed		3	3	3	3
		Air Flow (Hi)	CFM (m³/hr)	295 (500)	470 (800)	530 (900)	885 (1500)
		Noise Level	Lo-Hi dBA	30 - 40	42 - 46	42 - 48	48 - 53
		Motor Input	Watts	40	49	54	105
Coil Type: Al. Fins; Tubes; P- Plain; G- Grooved	Grooved Copper Tubes - Aluminum Hydrophilic Fin						
Air Filter	Cleanable Cartridge Type						
Electrical	Voltage	208-230/1/60					
	Range	min 187 - max 253					
	FLA		0.18	0.22	0.25	0.48	
Controls	LCD Wireless Remote Control						
Refrigerant Connections inches (mm)	Type	Flare					
	Liquid		1/4 (6)	1/4 (6)	1/4 (6)	1/4 (6)	
	Suction		3/8 (10)	1/2 (13)	1/2 (13)	5/8 (16)	
	Drain Connections inches (mm)		3/4 (19)	3/4 (19)	3/4 (19)	3/4 (19)	
Dimensions inches (mm)	Height		7 5/8 (195)	8 1/2 (215)	8 1/2 (215)	9 5/8 (245)	
	Width		29 1/3 (745)	35 1/2 (900)	35 1/2 (900)	51 1/8 (1300)	
	Depth		9 7/8 (250)	11 1/5 (292)	11 1/5 (292)	13 1/8 (332)	
Net Weight lbs (kgs)		20 (9)	29 (13)	31 (14)	49 (22)		
O U T D O O R	MODEL NO.	32HE	012C 24-035BGC	018C 24-053BHC	024C 24-070BHC	036C 24-105BHC	
	Compressor Type	Rotary					
	Fan	No of Fans		1	1	1	1
		Noise Level (dba)		54	54	54	59
		Motor Amps	FLA	0.36	0.33	0.52	1.05
		Motor Input	Watts	72	72	115	230
	Refrigerant Connections inches (mm)	Type	Flare				
		Liquid		1/4 (6)	1/4 (6)	1/4 (6)	1/4 (6)
		Suction		3/8 (10)	1/2 (13)	1/2 (13)	5/8 (16)
	Refrigerant R410A (oz./kg.)		22.2 / 0.63	31.7 / 0.90	35.3 / 1.0	81.1 / 2.3	
Coil Type:	Grooved Copper Tubes - Aluminum Blue Slit Fin						
Electrical	Voltage	208-230/1/60					
	Range (min- max)	min 187 - max 253					
	Compressor RLA (Amps)		5.40	9.95	10.5	18	
	Minimum Circuit Amps (MCA)		7.29	12.99	13.90	33.14	
	Max. Fuse Amps (MFA- MOCP)		10	10	20	40	
Dimensions inches (mm)	Height		21 1/4 (540)	21 1/4 (540)	23 1/5 (605)	31 (790)	
	Width		38 1/8 (715)	31 1/3 (795)	33 1/2 (850)	38 1/5 (970)	
	Depth		9 1/4 (235)	10 (255)	11 5/8 (295)	14 1/2 (370)	
			57.3 (26)	79.3 (36)	79.2 (36)	162.8 (74)	



DELTA Comfort Technologies LLC.
 3350 SW 148th Ave, Miramar, Florida.33027. USA
 Tel: 954 734 2708 Fax: 954 874 1699
www.deltacomforttechnologies.com
www.delta-dct.com

DCT Interamerica: Latin America-Mexico
info@dctinteramerica.com

DCT America: North America, Canada
info@dctamerica.com

DCT Europe: Europe, M.East, Africa
info@dcteu.com

DCT China: Asia, Pacific, Russia
info@dctchina.com